# WE'RE NOT JUST CREATING REMOTE CONTROLS, WE'RE CREATING A SAFER WORKPLACE.

**RX ES** 

### **Product Information**

## **RX ES Series**

#### **Standard Features:**

- Rugged and impact resistant enclosure
- Different bus communication
- Analog/Digital I/O's
- Quick connect/disconnect option

## **Typical Applications:**

- Mobile Applications
- Bus communication equipment
- Material Handling
- Overhead Cranes
- Work Platforms
- Container Handling
- Specialty Applications
- A wide range of other applications





| Housing                   | Impact Resistant Polymer Composite                          | Typical Operating  | Up to 100m (300ft) for =1GHz;</th  |
|---------------------------|---|--------------------|--|
| Housing:                  | impact Resistant Polymer Composite                          | Range:             | Up to 30m (131ft) for 2.4GHz   |
| Weight:                   | Up to 740 g (1.6lbs)  | Safety:            | 20-bit ADMO address scheme with up to 1 Million possibilities; Active & Passive STOP Function; Parity and Checksum; Safety Category 3 Compliant (STOP) |
| Dimensions:               | H: 131mm (5.2")<br>W: 165mm (6.5")                          |                    |  |
|                           | D: 65mm (2.6")  |                    |  |
| Environmental Protection: | IP 65 (Exceeds NEMA 12/13)                                  | Temperature:       | -20°C to +70 °C<br>(-4°F to +158°F)  |
| Antenna:                  | External via TNC connector                                  |                    |  |
| Power Supply:             | 12 - 24 VDC (1.5A hold)                                     | Humidity Range:    | 0 to 97% max. non-condensing   |
| I/O:                      | Selection of Bus Communication: ProfiNet Profibus RS485/232 | Response Time:     | Less than 100msec  |
|                           | Modbus DeviceNet Ethernet                                   | RF Baud Rate:      | Up to 9600 bps   |
| Outputs:                  | 2 NO potential free Stop relays                             | Frequencies:       | 4xxMHz, 8xxMHz, 9xxMHz,<br>2.4GHz  |
| Diagnostics:              | Stop alert;<br>Profi active                                 | RF Unit:           | Type CS Synthesized with multiple frequencies  |
| Protocols:                | Customized protocols available upon request                 | Standard Features: | Built-in quick disconnect<br>connector<br>Up to 16 transmitters can control<br>1 receiver;<br>Full Duplex feedback available;<br>Vibration mounts      |

#### **ABOUT HETRONIC:**

Since 1982 Hetronic Inc. has manufactured and delivered over 500,000 radio remote control systems to customers around the world. We are recognized leaders in providing the safest, most reliable industrial Safety Radio Remote Control (RRC) user interface solutions for process and equipment control applications. Every Hetronic system is designed and configured to customer specific application needs for safety, performance, reliability and productivity. With a global network of service locations in over 50 countries operators can count on Hetronic to be there when they need local and immediate service and support. Hetronic is committed to deliver turnkey radio remote control solutions that not only meet the highest standards for RF communication, but that also provide you with the newest technology and highest possible value to get the job done efficiently and safely in the harshest of environments.

Contact a Hetronic expert and learn more at  $\underline{www.hetronic.com}$ 





