

Receiver Type: RX-MFSHL AC8 RX-MFSHL AC16

Housing Material:

Fiber-enforced polycarbonate (PC)

Environmental Protection:

IP 65 (Exceeds Nema 12/13)

Weight:

AC8
0.9 lbs, 430 g

AC16
0.6 lbs, 290 g

Dimensions:

AC8
Length: 3.9 in., 98 mm
Height: 2.2 in., 56 mm
Depth: 3.4 in., 85 mm

AC16
Length: 5.7 in., 144 mm
Height: 2.2 in., 56 mm
Depth: 3.7 in., 94 mm

Antenna:

Internal

Power Supply:

48 VAC - 220 VAC single phase

LED Diagnostics:

Power/operation, transmission reception, Main Contact (MC) error, memory error

Inputs/Outputs:

RX-MFSHL AC8:

Outputs:

- 7 Solid state N.O. or N.C. outputs - 3 A max. Outputs fully programmable via H-Link
- 1 Solid state N.O or N.C. Main Contact (MC) output - 8 A max.

RX-MFSHL AC16:

Inputs:

- 3 On/Off inputs at 12 - 220 VAC or 12 - 300 VDC. Inputs fully programmable via H-Link

Outputs:

- 15 Solid state N.O. or N.C. outputs - 3 A max. Outputs fully programmable via H-Link
- 1 Solid state N.O or N.C. Main Contact (MC) output - 8 A max.

Frequency Range:

868 MHz / 916 MHz or 311 MHz / 315 MHz (Selectable via H-Link)

RF Unit:

Type MFS with single frequency, selectable duty cycle

Typical Operating Range:

Approximately 100 ft. (30 m) line of sight

Safety Address:

20-bit (over 999,999 individual possibilities)
Address learning receiver

Safety:

Active and passive Stop function
Parity & Checksum

Temperature Range:

-11° F . . . +158° F (-25° C . . . +70° C)

Humidity Range:

0 - 97% maximum non-condensing

Response Time:

Approx. 100 msec.

Baud Rate:

Up to 76.8 Kbps. (selectable via H-Link)

Standard Features:

Fully programmable via Pocket PC with H-Link modem
Built-in industry standard quick disconnect connector
Built-in warning device (horn) @ 96dB output
Main Contact (MC) short-circuit monitor protection

Standard Options:

Wall mount adaptor



RX-MFSHL AC8



RX-MFSHL AC16