



*IF YOU'VE GOT INDUSTRIAL EQUIPMENT TO MOVE  
WE'VE GOT THE REMOTE CONTROL TO MOVE IT.*



### Standard Features:

- Rugged, Field Tested IP65 Rated Case
- 12 Programmable Buttons (10 Front, 2 Side)
- Single and Dual Step Buttons
- STOP Button EN60204-1, ISO13850 Compliant
- Transmit Range >100m
- Frequency Operation: 4xxMHz, 8XXMHz, 2.4GHz
- Long Life Li-Polymer Battery
- 8 Feedback LED's (optional)
- Color 2.4" Backlit TFT Screen
- Operating Time >10 hrs.
- Command Response Time <100ms
- Weight: < 400g (< 0.88lbs)
- Cable Control Optional

Standard Features	
Front Buttons	Ten; User Programmable
Side Buttons	Two; User Programmable
Functions on Front Buttons	Single, Two Step
Start Button	One (1): any button; user programmable
Power Button	One (1)
Stop Button	EN60204-1, ISO13850 compliant
Transmission Type	>= 100m
Telegram Type	Standard or MFS
Frequency Operation	4xxMHz, 8xxMHz, 2.4GHz
Communication Mode	Half Duplex
Battery Low Voltage indicator	Red LED
Communication indicator	Green LED
Feedback	Color 2.4" TFT Backlit Display
Logic	PC H-Link programmable
Start-Interlock	Standard
Function Interlock	User Programmable
Command Response Time	< 100ms
Stop Function response time	< 100ms
Security	Over 1 million combinations
Mechanical	
Enclosure Material	Reinforced Polyamide polymer with rubber overmold
Weight, including battery	< 400g (0.88lbs.)
Push Button Lifetime	Minimum 1M cycles
Activation force first step	4N
Activation force second step	8N

Electrical	
Operating Voltage	3.3 to 4.0V
Current Consumption (idle)	150mA for half-duplex configuration
Current Consumption (max.)	220mA
Battery Type	Li-polymer
Battery Rating	3.6V 3000mAh
Operating Hours	>10 hrs.
RF output EIRP (50 Ohm)	10mW max.
Environmental	
Operating Temperature	-20° C to + 70° C
Storage Temperature	-40° C to + 75° C
IP Rating	Min IP65
Relative Humidity	95% IE C60068-2 -75
Ozone/Weather resistant	IEC 60068-2-11
Chemical Resistance	ISO16750
Shock Resistant	IEC 60068-2-29
Vibration Resistant	IEC 60068-2-64
Functional Safety	EN60204-1
Optional Features	
Infrared Systems	
Proportional Button(s)	
LED Feedback	Up to 8 LED's available
Memory Function (last 1000 operations)	
Full Duplex Transmission	
Carry Pouch	
Cable Control	RS232